

Proceedings of the Iowa Academy of Science

Volume 37 | Annual Issue

Article 83

1930

The Effect of Gas-Pressure on Tesla-Luminescence

G. M. Wissink

Burlington Junior College

Copyright ©1930 Iowa Academy of Science, Inc.

Follow this and additional works at: <https://scholarworks.uni.edu/pias>

Recommended Citation

Wissink, G. M. (1930) "The Effect of Gas-Pressure on Tesla-Luminescence," *Proceedings of the Iowa Academy of Science*, 37(1), 314-314.

Available at: <https://scholarworks.uni.edu/pias/vol37/iss1/83>

This Research is brought to you for free and open access by the Iowa Academy of Science at UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact scholarworks@uni.edu.

was made upon the resistance of the cortical layer transverse to the length of the tuber.

IOWA STATE COLLEGE,
AMES, IOWA.

THE EFFECT OF GAS-PRESSURE ON TESLA-LUMINESCENCE

G. M. WISSINK

In investigating the tesla-luminescence of cod-liver oil, it was observed that the nature of the luminescence would change very rapidly with the pressure. This effect was noticed for the cod-liver oil vapor, for carbon-dioxide and for air. In the case of air it was found that there was an abrupt change from a pinkish glow at about 4 mm. pressure to a bright orange at about 2 mm. The actual value of the pressure at which this effect took place has not as yet been accurately determined.

A preliminary spectroscopic study of the luminescence has shown that bands which are prominent at the higher pressure disappear at the lower.

BURLINGTON JUNIOR COLLEGE,
BURLINGTON, IOWA.

VELOCITY OF ULTRA-SONIC WAVES IN VAPOR

GEORGE E. THOMPSON

The velocity of sound waves having a frequency of 107,500 cycles per second has been measured in water vapor and in ether vapor. The waves are generated by a quartz crystal oscillator and velocities measured by an interference method similar to that used by Pierce.¹ The sound chamber is made air tight. After thorough exhaustion of the chamber with an air pump the vapor is introduced through a stop cock which connects the chamber with a glass bottle containing vapor. The sliding joint, through which the rod carrying the sound reflector passes, is made air tight by means of a rubber tube, which, by stretching and contracting, allows the reflector to be moved back and forth by a screw mounted outside the chamber.

The best value obtained for the velocity in water vapor is

¹ Proc. Am. Acad. 60, 271 (1925).